

DR-2200

- USB direct dictation device
- Symmetrical and ergonomic design for comfortable hold
- Engineered to work best with Dragon NaturallySpeaking speech recognition software
- Built-in volume control for convenience
- Multi-functional slide switch and trackball
- Directional microphone to reduce undesired background noises
- Powerful integrated speaker for clear playback
- 5 programmable buttons for customised workflow



DR-2100 + trackball

Olympus introduces the next generation of Directrec USB microphones. The new line of direct audio recording systems sets benchmarks in terms of its durable and ergonomic design, operability and excellent audio quality.

The DR-2200 has been designed for prolonged usage, with a smooth and rounded back for comfortable hold, in addition to a carefully considered interface layout featuring a multi-functional slide switch for one-thumb operation and a stainless steel trackball for extra-precise navigation. Even more the symmetrical design enables optimum handling for left and right-handed users. Besides maximum ease of use and efficiency, this device is equipped with a low-noise directional microphone to reduce undesired background noises and ensure the best results in speech recognition and transcription. The DR-2200 is engineered to work best with Dragon NaturallySpeaking speech recognition software and delivers perfect results that are more accurate than ever. A powerful and integrated speaker with digital volume control supports a clear playback.

Specifications

USB functionality

USB Speed	USB 2.0 Full Speed
-----------	--------------------

Device operation

Slide switch	Yes (Record/Stop/Play/Review)
Track ball	Yes
Function buttons	5

Technical Data

operating temperature	0-42°C / 32-107.6°F
-----------------------	---------------------

Other Features

Support barcode	No
Device management software	Yes (Download from Olympus website)

Interfaces Input

Microphone type	Electret condenser microphone
Microphone diameter	10mm
Frequency response	100 - 14.000Hz (with PCM recording)
Microphone sensitivity / gain	- 37dB at 1kHz
Input Level	- 45dBv
Microphone characteristics	Uni-directional
Signal-to-noise ratio	>71dBA

Interfaces Output

Max. working output	320 mW or more
Speaker Diameter	Built-in ø 28 mm round dynamic speaker
Acoustic frequency response	300 - 10.000Hz

Dimensions

Weight	201g
WxHxD	44.6 x 31.6 x 154mm
Green specification	Compliant to 2002/95/ EC(RoHS). Lead-free soldered product. Free of PVC and brominated flame retardants

Operating Systems & Requirements

Windows Operating System	Microsoft Windows XP SP3 (32bit/64bit) Microsoft Windows Vista Ultimate/ Enterprise/Business SP1 (32bit/64bit) Microsoft Windows 7 Ultimate/ Professional (32bit/64bit)
Macintosh Operating System	Mac OS X 10.4.11 - 10.6
CPU/RAM	At least meeting the minimum requirements for the operating system in use
USB port	One or more free ports